



EUROCEL MSK 6143

Short description:

General purpose masking tape

Product Data

Backing:	58 g/m ² natural white saturated crepe paper
Adhesive:	Dry natural rubber and resins solvent based
Total thickness	0.120 mm
Adhesion to steel	4 N/25mm
Tensile strength MD	75 N/25mm
Elongation at break	8,5 %
Temp. Resistance	60 °C (30 min)

Application

General purpose masking tape, suitable for all kinds of simple painting jobs. Tape must be applied at room temperature.

Features	Benefits
Dry natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">➤ Good adhesion even on irregular surfaces➤ Resistant to most common paints➤ Easy removal without adhesive residue
Saturated paper backing	<ul style="list-style-type: none">➤ Well conformable to most shapes➤ Compatible with most common paints and lacquers➤ Removable without breaking➤ Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss