Superplasma PL





Technical Details

EXTERNAL SHELL: P.P. Polypropylene INTERNAL SHELL: HD Polystyrene HEADBAND: Soft PA Nylon

(fixed to the external shell without metal rivets) SIZE: Universal-adjustable from 51 to 62 cm

STANDARD: EN 12492



420 g



-20°C / +35°C







AHE00005.202 YELLOW



AHE00005.203 ORANGE



AHE00005.204 RED



AHE00005.208 BLUE



AHE00005.209 ANTRACITE



AHE00005.21 BLACK

Technology



VENTILATION: Maximum ventilation thanks to the ten air intakes. The air intakes and the internal outflow channels guarantee effective breathability.



LAMP CLIPS: Helmet is equipped with strong external carrying clips, made of high intensity resin and frontal antislide insert that are compatible with all headlamps with elastic bands on the market.



ANTI-INTRUSION GRILLE: The air intakes are equipped with an anti-intrusion grille that prevents entry of debris whilst maintaining breathability.



CHINSTRAP EN 12492: Four point chinstrap with which is crossed at the back to secure the helmet to the head better. The safety release system allows quick fastening and opening of the locking mechanism in conformity with EN 12492. Provided with lateral divider for adjusting the length of the straps.



RING TO HOOK: Fitted with a special hook on the chinstrap which allows the helmet to be connected to the harness.



2DRY: This high-tech and maximum comfort fabric dries very quickly, encouraging the expansion and dispersion of moisture to the outside and leaving a pleasant feeling.



UP & DOWN SYSTEM: The innovative and exclusive UP & Down technology ensures a precise and comfortable fit around the neck. A center wheel and two side flaps allow quick adjustment of the helmet not only in width but also in height and tilt.



VISOR ATTACHMENT: Provided with attachment for fitting visors.




EARMUFFS FITTING: Built with bayonet adapter for earmuffs. Compatible with KASK earmuffs.

Superplasma PL

KAJK

Performances

PROTECTION AGAINST TOP IMPACTS	K	5 Kg from 2 m 100 J
PROTECTION AGAINST SIDE, FRONT AND REAR IMPACTS	K	5 Kg from 0,5 m 25 J
PROTECTION AGAINST THE PENETRATION OF OBJECTS	K	3 Kg from 1 m 30 J
CHIN STRAP RESISTANCE > 50 KG	K	
RETENTION SYSTEM EFFECTIVENESS	K	





Additional Information





GUARANTEE

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet). Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

When not in use the helmet should be stored away from direct sunlight or source of heat.

ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

Accessories



VAA/I00018 Visor V2 Plus



WVI00003 Visor FULL FACE



WVI00006 Mesh visor



WAC00003 Adapter for earmuffs



WPA00002 Inner padding



WAC00008 Visor carrier 30 mm attachment



WVI00005 WHP00004/5/6 Mesh visor carrier Earmuffs





Winter padding



WAC00020 Neck Shade



WAC00024 Neck Shade HI VIZ

